

## NASCAR H type front package

---

### options

---

- 11.8"x1.25" standard rotor
- 11.8"x1.25" light weight rotor
- Fixed drive or bobbin drive hat systems.
- Front or rear mount available

### Features and benefits

---

- Radial mount with adaptor bracket for accurate positioning.
- Optimum strength to weight ratio.
- Superior caliper cooling features.
- Externally insulated brake fluid bridge pipe.



### specifications

---

<b>Piston size</b>	1.625" / 1.50"
<b>Pad area</b>	40.00cm <sup>2</sup> / 6.20 in <sup>2</sup>
<b>Pad volume</b>	64.00cm <sup>3</sup> / 3.90 in <sup>3</sup>
<b>Pad thickness</b>	16mm / .629"
<b>Standard rotor 11.8"x1.25" / 48 vane</b>	9.95 lbs.
<b>Light weight rotor 11.8"x1.25" / 24 vane</b>	7.94 lbs.
<b>H type front caliper</b>	4.42 lbs.
<b>Fixed drive hat</b>	2.30 lbs.
<b>Bobbin drive hat</b>	2.30 lbs.
<b>Fixed drive hardware (axle set)</b>	0.786 lbs.
<b>Bobbin drive hardware (axle set)</b>	0.924 lbs.

### applications

---

NASCAR Nextel Cup, Busch Series and Craftsman Truck Series.

# NASCAR H type front package

## CALIPERS


**H-TYPE**  
**CAR6346H07ASLL & RL**




Bracket **BKC4463XG44**  
Service kit **CSK3841EB751**

## PADS

FERODO - **FRP218\***  
MINTEX - **1200\*\*\*16**  
PAGID - **U1749RS\***  
PFC - **7740.\*\*.16.4**



FERODO - **FRP219\***  
PAGID - **U2127RS\***  
PFC - **7745.\*\*.16.4**  
WILWOOD - **15A-5936K**




## ROTORS

11.81"x1.25" - 48 vane  
**DIV2146X428C48L & R**

11.81"x1.25" - 24 vane  
**DIV2137X428C48L & R**  
10x7.87" Bolt Circle

## HATS

FIXED OR BOBBIN DRIVE  
2.125" - **BAD2129X457**  
2.776" - **BAD2129X458**



## HARDWARE

BOBBIN DRIVE  
**BBK3625X004.10**

Kit contains:  
10 x BSD3430X401M  
10 x BSH0080X641  
10 x NSJ0080X441

FIXED DRIVE  
**BBK0621X001.10**

Kit contains:  
10 x BSS4474X637  
10 x W5F0080X114  
10 x NSB0080X063

SUPER SPEEDWAY

## Service parts

1.625" piston	<b>PAS4441X551</b>	bridge pipe	<b>PSC4463X656</b>
1.625" piston seal	<b>SE54100X751</b>	recirculator kit	N/A
1.50" piston	<b>PAS4438X551</b>	bleed screw	<b>FSB0080X008</b>
1.50" piston seal	<b>SE53800X751</b>	caliper temp. strips	<b>THS0080X285</b>

Updated 11/23/2004

**Alcon Components USA Inc.**  
T +1 (847) 788 0901  
F +1 (847) 788 0947  
E pstubbs@alconusa.com

**Alcon (Mooreville)**  
T +1 (704) 799 2723  
F +1 (704) 799 2287  
E jthomas@alconusa.com

